



CHRISTIE ENGINEERING

ABN 062468

High Powered Outback Battery Charger

GX16012V120A 12 VOLT 120 AMP PETROL

Also available in electric start



POWERED by
HONDA™

SPECIFICATIONS

Weight	26kg
Dimensions (mm)	510L x 385W x 380H
Engine	Honda GX160 air cooled
Alternator	Bosch 120 amp
Max eng. power	5.5hp @ 3600rpm
Fuel Capacity	3.6 Litres
Fuel Type	4-stroke unleaded petrol
Fuel Consumption	Approx. 3/4 Litres/hour
Oil Capacity	0.6 Litres
Starting System	Recoil or electric
Electric Output	12 Volts D.C
Max Voltage Low	14 Volts regulated
Max Voltage High	14.8 Volts regulated
Max Amp Output	120 Amps
Voltage Cut Out	18 Volts
Charge Indication	10mm LED

This larger model is best suited for larger charging requirements, such as the marine industry, backup for solar powered sites, motor-homes, earthmoving contractors, emergency services, mobile mechanics, communication repeaters, arrow boards, council machinery etc. Designed for the harsh environments of Australia, so no digital electronic components are installed on this model.

FEATURES

- Environmentally friendly Honda 5.5hp 4-stroke engine
- Low or high charge rate, by the flick of a switch
- Short circuit and over voltage protected
- Super bright LED charge indication light
- Lightweight, weighing only 26 kg
- 3m long heavy-duty high current leads & alligator clamps

USES

- Farmers can supply enough charge in as little as 5 minutes to start machinery.
- Run car fridges for 24 hours and charge your batteries in as little as 1 hour.
- 12 Volt lighting or other appliances can be powered in emergency situations.

Note- some deep cycle batteries will not accept a fast charge & may require trickle charging for a long period of time.

ALSO AVAILABLE IN ELECTRIC START



**CHRISTIE
ENGINEERING**

Contact us with any further queries;



www.christieengineering.com.au



enquiries@christieengineering.com.au



(02) 9620 1208



123 Delaware Road Horsley Park
NSW 2175

